

Anderol[®] 5220 PLUS

Anderol[®] Industrial lubricants gears and bearings

Description

Advanced Technology Gear and Bearing Oils, EP

Anderol[®] 5220 PLUS EP Synthetic Gear Oil is particularly suited for gear applications requiring high micro pitting resistance. It is formulated using a specific balance of synthetic base stocks in order to provide performance greatly superior to conventional petroleum oils. **Anderol[®] 5220 PLUS EP** is fully compatible with petroleum based oils while offering significantly improved load carrying ability, excellent wear and rust protection, higher viscosity indices, higher flash points, low pour points, cleaner running systems, and improved thermal and oxidative stability which can extend lubricant life reducing maintenance costs.

Anderol[®] 5220 PLUS EP meets or exceeds the requirements of:

- AISE 224 (formerly USS 224)
- ANSI/AGMA 9005-E02 (EP)
- David Brown S1.53.106
- DIN 51517-3
- ISO 12925-1:1996 (type CKC)

Features and Benefits

- Superior oxidative and thermal stability compared to mineral oil.
- Wide operating temperature range.
- Lower maintenance costs.
- Excellent load carrying ability.
- Corrosion resistant.
- Extended lubricant life.
- Improved cleanliness.
- Compatible with paints, gaskets, and seals used with conventional petroleum based oils.
- Compatible with petroleum oils, therefore allowing minimal effort to changeover.

Compatibility

Anderol[®] synthetic hydrocarbon based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. The **Anderol[®] 5000 PLUS** series meets or exceeds the SBR-NBR28 seal requirements in the DIN 51517-3 specification. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an **Anderol[®]** synthetic hydrocarbon based lubricant.



Anderol[®] 5220 PLUS

Anderol[®] Industrial lubricants gears and bearings

Application

- Particularly suited to gear applications in extreme service conditions.
- All types of enclosed gear drives.
- Bearings, including plain, rolling elements and antifriction types.
- Applications requiring high micro pitting resistance.

Approval

- Flender (Siemens) Helical, Bevel and Planetary Gear Units and Geared Motors (Rev. 15)
- Maag Gear (FLSmidth) "Recommended Lubricants for Gearboxes and Toothed couplings", Doc No 60000208.
 - Hansen Industrial Transmissions (Sumitomo) "Acceptance of Lubricating Oils for Industrial Gear Units", BUI-TEC-2009-4-001.
- Fives Cincinnati P-Specifications (formerly Cincinnati Machine).
- Sumitomo Paramax Series gearboxes
- GE Off-Highway Vehicle Gearbox Oil D50E35 B, C, D, E
- Geremia Redutores Ltda.
- WEG-Cestari Redutores Ltda.
- Zanini Renk Equipamentos Industriais Ltda.
- Grupo TGM



Anderol[®] 5220 PLUS

Anderol[®] Industrial lubricants gears and bearings

Technical data*

PROPERTY	METHOD	ANDEROL 5220 PLUS
ISO VG	ASTM D-2422	220
AGMA Grade	AGMA 9005-D94	5EP
Viscosity @ 40°C, cSt	ASTM D-445	225
Viscosity @ 100°C, cSt	ASTM D-445	26
Viscosity Index	ASTM D-2270	150
Density @ 15.6°C, (60°F)	ASTM D-1250	0.86
Total Acid Number, mg KOH/g	ASTM D-664	0.7
Flash Point, °C	ASTM D-92	244
Pour Point, °C	ASTM D-97	-42
Foam Seq, I, II, III (ml/ml)	ASTM-892	10/0, 10/0, 0/0
Copper Corrosion	ASTM D-130	1b
Steel Corrosion	ASTM D-665A	Pass
Oxidation, % KV100 change	ASTM D-2893	2.7
4-Ball Wear, mm	ASTM D-4172	0.32
4-Ball EP	ASTM D-2783	
Load Wear Index, kgf		56.2
Weld Point, kg		250
FAG FE8, roller bearing wear	DIN 51819-3	
Weight loss Rollers, mg		4
Weight loss Cage, mg		29
FZG A/8.3/90, pass load stage	DIN 51354	≥14
FZG A/16.6/90, pass load stage	DIN 51354	≥14
Micro pitting resistance	FVA 54/7	High

*The analytical data are guide values.



Anderol[®] 5220 PLUS

Anderol[®] Industrial lubricants gears and bearings

Consult safety data sheet (SDS) for additional handling information on **Anderol[®] 5220 PLUS**
For registrations, certificates and approvals please refer to anderol.com

® = registered trade mark

This is a product of Anderol BV
Groot Egtenrayseweg 23
5928PA Venlo
The Netherlands
www.anderol.com

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2021 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America
+1.833.LANXESS
customer.care@lanxess.com

Europe, Middle East & Africa
+31.77.396.0340
customerservice@anderol.com

South & Central America
+55.19.3522.5083
atendimento.cliente@lanxess.com

Asia Pacific
+86.21.6109.6666
Orders.apac@lanxess.com

