

ROYCO® 586

MINERAL BASED GEAR LUBRICATING OIL

ROYCO® 586 Grades L and M are highly refined petroleum oil based lubricants formulated with modern additives to provide oxidation and corrosion protection, high load carrying, antifoaming, as well as high viscosity index for both low and high temperature fluidity.

ROYCO® 586 is available in viscosity grades L (light) and M (medium).

APPLICATIONS

ROYCO® 586 is recommended for lubrication of gears exposed to light to moderate load and low to moderate speed applications. Grade L is intended for use in low temperature environments and Grade M is intended for use in moderate to warm climates. ROYCO® 586 is particularly suitable for the lubrication of helicopter gearboxes as well as general-purpose industrial applications requiring an E.P. lubricant for heavily loaded gears.

FEATURES AND BENEFITS

Features

- **Outstanding Extreme Pressure Characteristics**
- **Rust, oxidation and corrosion inhibition**
- **High Viscosity Index**

Benefits

- **Protects gears in a wide temperature range even in light-to-medium gear trains or gear boxes that operate in low-to-medium speeds down to -40°C.**

APPROVALS AND SPECIFICATIONS

ROYCO® 586 Gr. L and Gr. M meets all requirements of and is qualified to MILSPEC: MIL-PRF-6086F Grades L and M. NATO Codes NATO O-153 and O-155 respectively.



TYPICAL PROPERTIES

PROPERTIES	TEST METHOD	ROYCO® 586	
		GRADE L	GRADE M
Kinematic Viscosity, cSt	ASTM D445		
@ 37.8°C (100°F)		26.63	73.9
@ 98.9°C (210°F)		4.97	9.18
Viscosity Index	ASTM D2270	123	111
Flash Point, °C	ASTM D92	173	187
Acid Number, mq KOH/g	ASTM D974	0.13	0.06
Load Wear Index, kg	ASTM D-2783	46.8	52.2
Foam Resistance, ml initial/final	ASTM D892		
Sequence I		1/0	1/0
Sequence II		14/0	13/0
Sequence III		3/0	1/0
Gravity, API	ASTM D287	28.9	23.2
Density, pounds per gallon		7.346	7.587
Precipitation Number	ASTM D91	0.00	0.00
Copper Corrosion, 100°C, 3 Hrs	ASTM D130	1B	1B
ASTM Color	ASTM D1500	1.5	1.8
Pour Point, °C	ASTM D97	-44	-38

PACKAGING

ROYCO® 586 Grade L and Grade M are available in 5-gallon pails and 55-gallon drums.

Other package sizes may be available on special request.



A company of the
LANXESS
Group

The information contained herein relates to a specific Chemtura product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCTS CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.

The Chemtura logo is a trademark of Chemtura Corporation or one of its subsidiaries.

Copyright © 2016 Chemtura Corporation. All rights reserved.

North America

+1.800.325.6252
customer.care@chemtura.com

Europe, Middle East & Africa

+44.161.875.3800
emea.export@chemtura.com

South & Central America

+55.19.3522.5000
Atendimento.cliente@chemtura.com

Asia Pacific

+86.21.3866.6509
orders.apac@chemtura.com

